High Value Tray Cart

ALLIANCE PRODUCTS
High-value stainless steel and aluminum equipment

Specifications

- Stainless steel is nickel-bearing, 200 series minimum. This material is NSF recognized for corrosion resistance.
- Body available in .063 aluminum or 18 gauge stainless steel.
- Single door design with full length hinge and heavy duty stainless steel gravity latch.
- Door opens a full 270 degrees and lays neatly against side of cart. Door is made of .090 aluminum or 16 gauge stainless steel.
- Contour seamless tray slides are easily removable for better cleaning. Available for 15x20 or 14x18 trays. Tray size must be specified with order.
- Base is made from .125 aluminum or 14 gauge stainless steel.
- Dual, vertical push/pull handles are mounted on rear of cart.
- Cart has 6" diameter cushion casters with zerk fittings (two swivel with brakes and two rigid).
- Full perimeter bumper is attached to cart base assembly.
- 5" ledge spacing.
- Ledges are 1 3/16" wide.
- Non-insulated, non-heated cart.

Options

- Please contact our facility at 615-895-5333 with inquiries for custom tray sizes, capacities, and ledge spacing.

NSF

Dimensions

Model	Height	(14x18) W	(14x18) D	(15x20) W	(15x20) D	Casters		Construction	Capacity	Shipping Weight
						Type	Dia.		Trays	lbs.
HM20	60 1/8"	27 3/4 "	35 1/2 "	27 3/4 "	35 1/2"	4 swivel, 2 w/brake	6"	Aluminum	20	140
HM24	70 1/8"	27 3/4 "	35 1/2 "	27 3/4 "	35 1/2"	4 swivel, 2 w/brake	6"	Aluminum	24	155
HM20SS	60 1/8"	27 3/4 "	35 1/2 "	27 3/4 "	35 1/2"	4 swivel, 2 w/brake	6"	Stainless Steel	20	220
HM24SS	70 1/8"	27 3/4 "	35 1/2 "	27 3/4 "	35 1/2"	4 swivel, 2 w/brake	6"	Stainless Steel	24	250