


HD Universal Angle Rack



Specifications

- Stainless steel is nickel-bearing, 200 series minimum. This material is NSF recognized for corrosion resistance.
- Standard uprights formed of 16 gauge stainless steel for strength and durability.
- Universal Angle Racks are equipped with 6 1/4" wide by 2 1/2" .090 aluminum ledges with a shoulder rivet in each end. Teardrop slots are incorporated into rack uprights to accept shoulder rivets in ledges. Teardrop slots are spaced 1 1/2" o.c.; ledges are furnished on 4 1/2" centers.
- Solid seamless aluminum top and bottom are hemfolded to fit over rack sides and are attached to uprights with 1/4" rivets.
- Racks are mounted on 5" diameter heavy duty swivel plate casters with polyurethane tread, mounted on 12 gauge galvanized reinforcing channels.



Universal angle



Dimensions

| Model | Tray Capacity | | Ledge Spacing | Overall Size | | | Casters | | Shipping Weight |
|--------|---------------|---------------------------|---------------|--------------|-----|---------|---------------------|------|-----------------|
| | | | | W | D | H | Type | Dia. | lbs. |
| A6913U | 13 & 26 | 18"x26", 12"x20" & others | 4 1/2" | 26" | 27" | 69" | 4 swivel, 2 w/brake | 5" | 120 |
| A6311U | 11 & 22 | 18"x26", 12"x20" & others | 4 1/2" | 26" | 27" | 63 1/2" | 4 swivel, 2 w/brake | 5" | 105 |