

HD Universal Angle Rack


ALLIANCE



1-800-522-3973

Specifications

- Stainless steel is nickel-bearing, 200 series minimum. This material is NSF recognized for corrosion resistance.
- Standard uprights formed of 16 gauge stainless steel for strength and durability.
- Universal Angle Racks are equipped with 6 1/4" wide by 2 1/2" .090 aluminum ledges with a shoulder rivet in each end. Teardrop slots are incorporated into rack uprights to accept shoulder rivets in ledges. Teardrop slots are spaced 1 1/2" o.c.; ledges are furnished on 4 1/2" centers.
- Solid seamless aluminum top and bottom are hemfolded to fit over rack sides and are attached to uprights with 1/4" rivets.
- Racks are mounted on 5" diameter heavy duty swivel plate casters with polyurethane tread, mounted on 12 gauge galvanized reinforcing channels.



Universal angle



Dimensions

Model	Tray Capacity		Ledge Spacing	Overall Size			Casters		Shipping Weight
				W	D	H	Type	Dia.	lbs.
A6913U	13 & 26	18"x26", 12"x20" & others	4 1/2"	26"	27"	69"	4 swivel, 2 w/brake	5"	120
A6311U	11 & 22	18"x26", 12"x20" & others	4 1/2"	26"	27"	63 1/2"	4 swivel, 2 w/brake	5"	105

© 2011 Alliance Products, LLC
 820 Esther Lane | Murfreesboro, TN 37129
 1.800.522.3973 toll free
 615.895.5333 phone
 615.895.5334 fax